


236 Satin

Non Transparent





Offering subtle privacy with good levels of solar protection

Features

- Part of the Verosol Core Collection fabrics developed in Europe, to the highest quality standard
- Constructed from 100% polyester, offering privacy and a good level of heat and light control
- Anti-static and easy to clean, making it ideal for bathrooms
- Suitable for Roller and Pleated Blinds

Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, use a soft feather duster or vacuumclean with a soft brush in a low setting.

For more information or to create your specification visit verosolspecifications.com.au or call 1800 721 404













236 Satin

Non Transparent

Fabric Density	Non Transparent						
Composition	100% Polyester	PVC free	Phthalate free	Formaldeh	yde free	Halogen free	Antimicrobial free
Weight	94gsm ± 5%	•••••				• • • • • • • • • • • • • • • • • • • •	••••••
Thickness	0.16mm ± 5%	•••••	• • • • • • • • • • • • • • • • • • • •		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	••••••
Width	2200mm ± 50mm	•••••	• • • • • • • • • • • • • • • • • • • •			• • • • • • • • • • • • • • • • • • • •	•••••••
Colour Fastness	≥ 5 [ISO 105 B02], Scale of 8	•••••	• • • • • • • • • • • • • • • • • • • •			• • • • • • • • • • • • • • • • • • • •	•••••••••••••••••••••••••••••••••••••••
Certification	Greenguard Gold	Oeko-Tex 10	0 Class IV	REACH	RoHS2	ISO 9001:2015	ISO 14001:2015
Suitable Products	Pleated Blinds	Roller Blinds	;			• • • • • • • • • • • • • • • • • • • •	

Fabric colour code	0000
Solar transmittance	40%
Solar reflectance outside	57%
Solar absorptance	3%
Luminous transmittance [VLT]	40%
UV transmittance	19%
Openness factor (nominal)	0%
Ra (colour rendering index)	99

Glazing Type - Single 4mm Clear Glass

Visible light transmittance	35%
G-value / Solar heat gain coefficient	40%
Shading coefficient	46%
U-value (W/m²K)	2.7

Glazing Type - High Performance Glazing

Visible light transmittance	29%
G-value / Solar heat gain coefficient	21%
Shading coefficient	24%
U-value (W/m²K)	0.9

Colour Range

