

## 890 SilverScreen Originals

Blockout Metallised



Flame Retardant



Roller Blinds

*Flame retardant solution with superior heat and light control*

### Features

- Part of the Verosol Core Collection - metallised fabrics developed in Europe, to the highest quality standard
- Designed for maximum room darkening and total privacy
- Superior heat and glare control, excellent energy efficient solution
- Woven from 100% Polyester and is flame retardant
- Oeko-Tex and Greenguard Gold certified
- Suitable for Roller Blinds

### Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information or to create your next specification visit [verosol specifications.com.au](http://verosol specifications.com.au) or call **1800 721 404**



# 890 SilverScreen Originals

## Blockout Metallised

|  |  |                          |                |                   |                     |
|--|--|--------------------------|----------------|-------------------|---------------------|
| Fabric Density                           | Blockout   | Anti-Static              | Yes            |                   |                     |
| Composition                              | 100% Polyester                                   | PVC Free                 | Phthalate Free | Formaldehyde Free | Antimicrobials Free |
| Weight                                   | 325gsm ± 5%                                      |                          |                |                   |                     |
| Thickness                                | 0.33mm ± 5%                                      |                          |                |                   |                     |
| Width                                    | 2400mm ± 50mm                                    |                          |                |                   |                     |
| Colour Fastness                          | > 5 ISO Standard 105-B02                         |                          |                |                   |                     |
| Flame Retardancy<br>[AS/NZS 1530.3-1999] | Ignitability Index                               | 0                        | Range [0-20]   |                   |                     |
|  | Spread of flame Index                            | 0                        | Range [0-10]   |                   |                     |
|  | Heat evolved Index                               | 0                        | Range [0-10]   |                   |                     |
|  | Smoke developed Index                            | 5                        | Range [0-10]   |                   |                     |
| [AS/NZS 3837-1998]                       | Classification Group 2                           |                          |                |                   |                     |
| [International]                          | DIN 4102 B1 (D)   BS5867-2 (UK)   NFPA 701 (USA) |                          |                |                   |                     |
| Aluminium Adhesion                       | ISO 2409 Classification 0                        | IR Emissivity Metal Side | 0.29           |                   |                     |
| Certifications                           | Greenguard Gold                                  | Oeko-Tex 100 Class IV    | ISO 9001:2015  |                   |                     |
|  | ISO 14001:2015                                   | REACH                    | ROHS2          |                   |                     |
| Suitable Products                        | Roller Blinds                                    |                          |                |                   |                     |

| Fabric colour code           | All Colours |
|------------------------------|-------------|
| Solar transmittance          | 0%          |
| Solar reflectance outside    | 70%         |
| Solar absorptance            | 30%         |
| Luminous transmittance [VLT] | 0%          |
| UV transmittance             | 0%          |
| Openness factor (nominal)    | 0%          |

### Glazing Type - Single 4mm Clear Glass

|                                       |     |
|---------------------------------------|-----|
| Visible light transmittance           | 0%  |
| G-value / Solar heat gain coefficient | 22% |
| Shading coefficient                   | 25% |
| U-value (W/m <sup>2</sup> K)          | 2.1 |

### Glazing Type - High Performance Glazing

|                                       |     |
|---------------------------------------|-----|
| Visible light transmittance           | 0%  |
| G-value / Solar heat gain coefficient | 16% |
| Shading coefficient                   | 18% |
| U-value (W/m <sup>2</sup> K)          | 0.8 |

### Colour Range

