

## 734 Tempest

Semi Transparent



Roller Blinds



Roman Blinds



Panel Glides

*Intricate and elegant collection with matching blackout fabric*

### Features

- Intricate weave construction with multi-coloured yarns, creating depth and texture
- Combination of thick and thin yarns adds a decorative touch
- Featuring a neutral palette of 13 colours, and available in matching blackout fabric
- Suitable for Roller Blinds, Roman Blinds and Panel Glides

### Care Instructions

Wipe clean with warm soapy water and a damp cloth.

For more information or to create your next specification visit [verosol specifications.com.au](https://verosol specifications.com.au) or call **1800 721 404**



Green Building  
Council Australia  
Member 2023-2024

# 734 Tempest

## Semi Transparent

|  |  |                       |              |
|--|--|-----------------------|--------------|
| Fabric Density                           | Semi Transparent   |                       |              |
| Composition                              | 100% Polyester   | PVC Free              |              |
| Weight                                   | 220gsm ± 5%  |                       |              |
| Thickness                                | 0.55mm ± 5%  |                       |              |
| Width                                    | 3000mm   |                       |              |
| Colour Fastness                          | >5 [Blue Wool Scale], Fade Resistant                       |                       |              |
| Flame Retardancy<br>[AS/NZS 1530.3-1999] | Compliant with BCA requirements for class 2 to 9 buildings |                       |              |
| Certification                            | Greenguard Gold  | Oeko-Tex 100 Class IV |              |
| Suitable Products                        | Roller Blinds  | Roman Blinds          | Panel Glides |

| Fabric colour code           | 1000 | 1500 | 2000 | 3000 | 4000 | 5000 | 6000 | 7000 | 8000 | 9000 |
|------------------------------|------|------|------|------|------|------|------|------|------|------|
| Solar transmittance          | 46%  | 46%  | 33%  | 40%  | 37%  | 25%  | 17%  | 10%  | 13%  | 7%   |
| Solar reflectance outside    | 54%  | 53%  | 64%  | 48%  | 42%  | 34%  | 21%  | 11%  | 17%  | 8%   |
| Solar absorptance            | 0%   | 1%   | 3%   | 12%  | 21%  | 41%  | 62%  | 79%  | 70%  | 85%  |
| Luminous transmittance [VLT] | 47%  | 47%  | 39%  | 39%  | 34%  | 21%  | 15%  | 9%   | 11%  | 6    |
| UV transmittance             | 33%  | 34%  | 27%  | 28%  | 24%  | 15%  | 11%  | 8%   | 9%   | 5%   |
| Openness factor [nominal]    | 0%   | 4%   | 3%   | 5%   | 4%   | 3%   | 4%   | 5%   | 4%   | 4%   |

### Glazing Type - Single 3mm Clear Glass

|                                       |     |     |     |     |     |     |     |     |     |     |
|---------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| G-value / Solar heat gain coefficient | 46% | 47% | 49% | 49% | 52% | 55% | 61% | 66% | 63% | 68% |
| Shading coefficient                   | 53% | 54% | 56% | 56% | 60% | 63% | 70% | 76% | 72% | 78% |

### Colour Range

