Verosol

737 Veropaque G3

Blockout



Contemporary and soft to touch, with matching semi transparent fabric

Features

- Constructed from a fine 2x1 weave, making it delicate to touch
- Colour coated backing for a uniform look from the inside and outside
- Designed for maximum room darkening and total privacy
- Flame retardant, Greenguard Gold, Oeko-Tex certified fabric suitable for commercial and residential
- Contemporary palette of 9 colours, and available in matching semi transparent fabric
- Suitable for Roller Blinds and Panel Glides

Care Instructions

Wipe clean with warm soapy water and a damp cloth.

For more information or to create your next specification visit verosolspecifications.com.au or call 1800 721 404



737 Veropaque G3 Blockout

Composition 100% Polyester with Acrylic Foam Coating PVC Free Air Quality ASTM-D5116 Weight 350gsm ± 10% Total Volatile Org. emission rate 0.00			
	03mg/m ² /hr		
Thickness 0.38mm ± 10%			
Width 3000mm			
Colour Fastness >5 [Blue Wool Scale], Fade Resistent			
Flame Retardancy Ignitability Index 14 Range [0-20]			
[AS/NZS 1530.3-1999] Spread of flame Index 0 Range [0-10] Compliant to BCA C1.10.			
Heat evolved Index 1 Range [0-10] Suitable for use in class 2 to 9 buildings.			
Smoke developed Index 7 Range [0-10]			
Certification Greenguard Gold Oeko-Tex 100 Class IV			
Suitable Products Roller Blinds Panel Glides			

Blackout Fabric Range	1000	1800	2000	4000	6000	6500	7000	8000	8500
Solar transmittance	0%	0%	0%	0%	0%	0%	0%	0%	0%
Solar reflectance outside	85%	62%	72%	46%	60%	54%	15%	11%	5%
Solar absorptance	15%	38%	28%	54%	40%	46%	85%	89%	95%
Luminous transmittance [VLT]	0%	0%	0%	0%	0%	0%	0%	0%	0%
UV transmittance	0%	0%	0%	0%	0%	0%	0%	0%	0%
Openness factor	0%	0%	0%	0%	0%	0%	0%	0%	0%

Glazing Type - Single 4mm Clear Glass									
G-value / SHGC	27%	37%	37%	46%	38%	42%	63%	66%	68%

Glazing Type - High Performance Glazing									
G-value / SHGC	24%		25%		26%	26%	30%	30%	30%

Colour Range

Colour Range							
1000 White	1800 White Stone	2000 White Bone	4000 Linen Bronze	6000 White Silver	6500 White Grey	7000 Black Beige	8000 Charcoal Grey



8500 Charcoal Black

© Copyright 2022 Verosol Australia [ABN 36 006 221 003] Updated March 2024 Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. All presented data calculated in WIS 3.0.1 (Advanced Windows Information System) with spectral data. Specifications and other data are based on information available at the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Flame retardancy information is sourced from AWTA testing results [AS/XES 1530.3:1999]. Please note that test results may vary slightly depending on fabric colour. [4mm Single Glass reference glazing A EN 14501], [High Performance Glazing reference glazing D EN 14501] according to EN 14500. Note: All colours are representative only, please request an A4 sample for accurate colour representation at www.verosol.com.au.