793 Earth Blockout

Blockout Non Metallised





Environmentally focused blockout with matching coloured backing

Features

- Part of the Verosol Core Collection developed in Europe to the highest quality standard
- PVC Free blockout with woven screen-like construction, flame retardant fabric with a decorative textile appearance
- · Coloured acrylic blockout backing
- · Greenguard Gold and Oeko-Tex certified
- Suitable for Roller Blinds

Care Instructions

For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information visit verosol.com.au or call 1800 721 404









793 Earth Blockout

Blockout Non Metallised

Fabric Density	Blockout	PVC Free	Formaldehyde Free	Lead Free	Phthalate Free
Composition	100% Polyester	•			
Weight	500gsm ± 10%	•••••			•••••
Thickness	0.60mm ± 5%	••••••			•••••••••••••••••••••••••••••••••••••••
Width	3000mm	•••••			• • • • • • • • • • • • • • • • • • • •
Flame Retardancy [AS/NZS 1530.3-1999]	Ignitability Index	16 Range [0-20]			• • • • • • • • • • • • • • • • • • • •
	Spread of Flame Index	0 Range [0-10]	•••••••	******	• • • • • • • • • • • • • • • • • • • •
Flame Retardancy [NFPA 701]	Heat Evolved Index	1 Range [0-10]			• • • • • • • • • • • • • • • • • • • •
	Smoke Developed Index	8 Range [0-10]	•••••••	*******	• • • • • • • • • • • • • • • • • • • •
AS/NZS 1530.3-1999]	Flamability Index	2	• • • • • • • • • • • • • • • • • • • •		•••••
[AS/NZS 3837-1998]	Group Classification	2	••••••		• • • • • • • • • • • • • • • • • • • •
[International]	NFPA 701	•••••			• • • • • • • • • • • • • • • • • • • •
Certification	Greenguard Gold	Oeko-Tex 100 Class II	ISO 9001:2015	ISO 14001:2015	• • • • • • • • • • • • • • • • • • • •
Suitable Products	Roller Blinds				

Fabric colour code	1000	8200	9000
Solar transmittance	0%	0%	0%
Solar reflectance outside	74%	18%	6%
Solar absorptance	26%	82%	94%
Luminous transmittance [VLT]	0%	0%	0%
UV transmittance	0%	0%	0%
Openness factor (nominal)	0%	0%	0%

Glazing Type - Single 4mm Clear Glass

Visible light transmittance	0%	0%	0%
G-value / Solar heat gain coefficient	28%	61%	68%
Shading coefficient	33%	71%	80%

Glazing Type - High Performance Glazing

Visible light transmittance	0%	0%	0%
G-value / Solar heat gain coefficient	24%	29%	30%
Shading coefficient	75%	91%	95%

Colour Range

